

Appl. No.: 10/069,260.  
Filed: February 22, 2002  
Page 2

Amendments to the Claims:

Claims 1-28 (cancelled)

29. (currently amended) A light source comprising  
a bulb having an inner surface and an outer surface,  
a filament mounted within said bulb and which includes a  
flat section, with said filament comprising tantalum carbide,  
a heating device for the filament whereby the filament  
can be heated to cause the emission of both visible light and  
heat radiation, and  
a dielectric multilayer coating positioned entirely on  
the inner surface of the bulb, said dielectric multilayer  
coating being spectrally selective so as to substantially  
reflect the heat radiation of the filament while substantially  
transmitting the visible light thereof.

---

30. (previously presented) The light source of Claim 29  
wherein the filament comprises a sintered metal powder.

31.-33. (cancelled)

34. (previously presented) The light source of Claim 29  
wherein said filament is coated with a coating material which  
has a higher melt temperature than the filament.

35. (previously presented) The light source of Claim 34  
wherein the coating material on said filament is selected from  
the group consisting of tantalum carbide, rhenium carbide,  
niobium carbide, zirconium carbide, and mixtures thereof.

Appl. No.: 10/069,260  
Filed: February 22, 2002  
Page 3

36. (previously presented) The light source of Claim 29 wherein the flat section of said filament comprises a strip with two longitudinal sides.

37. (previously presented) The light source of Claim 36 wherein two surface elements project from each of the respective longitudinal sides of the strip in the form of wings.

38. (previously presented) The light source of Claim 37 wherein each of the surface elements projects from the strip at an angle of about 90°.

39. (previously presented) The light source of Claim 29 wherein the flat section of the filament is substantially planar.

---

40. (previously presented) The light source of Claim 29 wherein the flat section of the filament is in the form of at least a portion of a cylindrical jacket.

41. (previously presented) The light source of Claim 40 wherein the at least a portion of a cylindrical jacket includes a lengthwise extending opening.

42. (currently amended) The light source of Claim 40 wherein the at least a portion of a cylindrical jacket defines a diameter which is ~~only slightly~~ smaller than a diameter defined by the bulb.

Appl. No.: 10/069,260  
Filed: February 22, 2002  
Page 4

43. (previously presented) The light source of Claim 40 wherein the bulb defines a longitudinal axis, with the filament being configured to define a coaxial center axis.

44. (previously presented) The light source of Claim 29 wherein the heating device comprises a pair of electrical contacts coupled to the filament for delivering an electrical current to the filament.

45. (cancelled)

46. (previously presented) The light source of Claim 29 wherein the flat section of the filament is of inverted U-shaped configuration to define two longitudinal sides which are almost back to back and which are integrally coupled at upper ends thereof, and wherein the heating device includes a pair of electrical contacts joined to respective ones of the longitudinal sides adjacent the opposite ends thereof.

47. (previously presented) The light source of Claim 46 wherein the two longitudinal sides are each in the form of a U-shaped channel section.

48.-49. (cancelled)